RECEIVED CENTRAL FAX CENTER

OCT 2 8 2005

Law Offices of

SENNIGER POWERS

One Metropolitan Square, 16th Floor St. Louis, Missouri 63102

Telephone (314) 231-5400 Facsimile (314) 231-4342

FACSIMILE TRANSMITTAL COVER SHEET

DATE: October 28, 2005 ATTORNEY DOCKET NUMBER: KCC 4771 PTO FACSIMILE NUMBER: (571) 273-8300
PLEASE DELIVER THIS FACSIMILE TO: <u>Examiner Karin M. Reichle</u> THIS FACSIMILE IS BEING SENT BY: <u>Kurt F. James</u> NUMBER OF PAGES: 23 INCLUDING COVER SHEET
TIME SENT: 4:45 p.m. OPERATOR'S NAME Brenda Witschorek
CERTIFICATION OF FACSIMILE TRANSMISSION
I hereby certify that this paper is being facsimile transmitted to the Patent and Trademark Office on the date shown below.
Brenda C. Witschorek Typed or printed name of person signing certification
Signature 10/28/05 Date
Type of paper transmitted: Appeal Brief OIPE/IAP
OCT 3 1 2005
Applicant's Name: Robert L. Popp et al.
Serial No. (Control No.): 10/038,818 Examiner: Reichle
Filing Date: 12/31/01 Art Unit: 3761 Confirmation No.: 9058
Application Title: MECHANICAL FASTENING SYSTEM FOR AN ABOSRGENT ARTICLE
IF YOU DO NOT RECEIVE ALL PAGES CLEARLY, CALL BACK AS SOON AS POSSIBLE. CONFIRMING NUMBER IS (314) 231-5400.

RECEIVED **CENTRAL FAX CENTER**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

OCT 28 2005

Application of Robert L. Popp et al. Art Unit 3761 Serial No. 10/038,818 Filed December 31, 2001 Confirmation No. 9058 FOR MECHANICAL FASTENING SYSTEM FOR AN ABSORBENT ARTICLE Examiner Karin M. Reichle

APPEAL BRIEF

Kurt F. James, Reg. No. 33,716 SENNIGER POWERS One Metropolitan Square, 16th Floor St. Louis, Missouri 63102 (314) 231-5400

TABLE OF CONTENTS

TABLE OF AUTHORITIES
REAL PARTY IN INTEREST
REAL PARTY IN INTEREST
II. RELATED APPEALS AND INTERFERENCES
III. STATUS OF CLAIMS1
IV. STATUS OF AMENDMENTS2
V. SUMMARY OF CLAIMED SUBJECT MATTER
VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL3
VII. ARGUMENT4
A. Claims 19 and 25 are unanticipated by Hetzler4
Claim 194
Claim 2510
B. Claims 3, 19-20, and 25 are patentable over U.S.
Patent Nos. 5,883,028 (Morman '028), and thereby
5.116.662 (Morman '662) and 5,114,781 (Morman '781), in
view of Hetzler10
Claim 1910
Claim 2514
Claim 25
VIII. CONCLUSION
CLAIMS APPENDIX16
EVIDENCE APPENDIX19
RELATED PROCEEDINGS APPENDIX19
KUTUTUR TITACHTE IN THE TELEVISION OF THE TELEVI

TABLE OF AUTHORITIES

_	-	-	_	_	\mathbf{E}	Ψ.	~	77	~
ĸ	ю.	ы.	и:	к	Pi.	N	∟.	ш	2

	Sensory Publishing, Inc., Manual of Patent Examining Procedure, 8th Ed., Rev. Two (2004), §2143.0111
CASE	s ·
	In re Arkley, 455 F.2d 586, 587 (CCPA 1972)
	In re Kotzab, 55 USPQ2d 1313, 1317 (Fed. Cir. 2000)11
	In re Mills, 916 F.2d 680, 682, 16 U.S.P.Q.2d 1430, 1432 (Fed. Cir. 1990)
	In re Lalu, 747 F.2d 703, 705, 223 USPQ 1257, 1258 (Fed.

KCC 4771 (K-C 17,182) RECEIVED PATENT **CENTRAL FAX CENTER**

OCT 2 8 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of Robert L. Popp et al. Art Unit 3761 Serial No. 10/038,818 Filed December 31, 2001 Confirmation No. 9058 For MECHANICAL FASTENING SYSTEM FOR AN ABSORBENT ARTICLE Examiner Karin M. Reichle

October 28, 2005

APPEAL BRIEF

This is an appeal from the final rejection of the claims of the above-identified application as set forth in the final Office action dated July 21, 2005. A Notice of Appeal was filed on August 30, 2005.

I. REAL PARTY IN INTEREST

The real party in interest in connection with the present appeal is Kimberly-Clark Worldwide, Inc. of 401 N. Lake Street, Neenah, Wisconsin 54957-0349, a corporation of the state of Delaware, owner of a 100 percent interest in the pending application.

II. RELATED APPEALS AND INTERFERENCES

Appellant is unaware of any pending appeals or interferences which may be related to, directly affect or be directly affected by, or have a bearing on, the Board's decision in the pending appeal.

III. STATUS OF CLAIMS

Claims 3, 19-23 and 25 are pending in the application. All of the pending claims stand rejected. Claims 1, 2, 4-18,

and 24 were previously cancelled. A copy of the pending claims appears in the Claims Appendix of this Brief.

Claims 19 and 25 stand rejected under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 5,910,136 (Hetzler).

Claims 3 and 20 stand rejected under 35 U.S.C. §102(b) as being anticipated by Hetzler, or alternatively, obvious in view of Hetzler under 35 U.S.C. §103(a).

Claims 3, 19-20, and 25 stand further rejected under 35 U.S.C. §103(a) as being unpatentable over U.S. Patent No. 5,883,028 (Morman '028), and thereby U.S. Patent Nos. 5,116,662 (Morman '662) and 5,114,781 (Morman '781), in view of Hetzler.

Claims 21-23 stand rejected under 35 U.S.C. 103(a) as being unpatentable over Hetzler in view of U.S. Patent No. 4,963,140 (Robertson) or Morman '028, and thereby Morman '662 and Morman '781, in view of Hetzler and Robertson.

STATUS OF AMENDMENTS IV._ No amendments have been filed after the final rejection.

V. SUMMARY OF CLAIMED SUBJECT MATTER

The following summary correlates claim elements to specific embodiments described in the application specification, but does not in any manner limit claim interpretation. Rather, the following summary is provided only to facilitate the Board's understanding of the subject matter of this appeal.

The present invention is directed to a mechanical fastening system 80 for an article 20. See page 21, lines 25 and 26, and Figs. 1-5. The fastening system 80 generally comprises a loop component 84, 85 mountable on the article 20 and capable of elastic stretching in at least two directions.

See page 22, lines 4-7, Figs. 1-5. The loop component 84, 85. is capable of being elastically stretched in at least one of the directions at least about 2.0 times a relaxed length of the loop component. See page 35, line 26 through page 36, line 15. The loop component 84, 85 comprises a neck-stretched non-woven material and an elastic substrate. See page 26, lines 22-25, page 28, lines 27-28, and Fig. 6. The elastic substrate is elastically stretchable in at least two directions. See page 27, lines 6-8. The non-woven material is attached directly to the elastic substrate. See page 34, lines 11-13 and Fig. 7. A hook component 82, 83 is mountable on the article 20 and capable of fastening engagement with the loop component 84, 85 to secure the article in a fastened configuration. See page 21, lines 25-29, page 22, lines 4-7, and Figs. 1 and 4. When the hook component 82, 83 is juxtaposed and engaged with at least a portion of the loop component 84, 85, the loop component is stretchable during limited movement of the loop component relative to the hook component. See page 26, line 22 through page 27, line 1.

- GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL VI. Appellant appeals the rejection of claims 19 and 25 under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 5,910,136 (Hetzler).
- B. Appellant further appeals the rejection of claims 3, 19-20, and 25 under 35 U.S.C. §103(a) as being unpatentable over U.S. Patent No. 5,883,028 (Morman '028), and thereby U.S. Patent Nos. 5,116,662 (Morman '662) and 5,114,781 (Morman '781), in view of Hetzler.

VII. ARGUMENT

A. Claims 19 and 25 are unanticipated by Hetzler.

Claim 19

Claim 19 is directed to a hook and loop mechanical fastening system for an article in which the loop component of the fastening system is mountable on the article and is capable of elastic stretching (e.g., elongating upon application of an elongating force and subsequent retraction upon removal or reduction of the elongating force) in at least two directions (e.g., a machine direction and a cross-machine direction of the loop component). In at least one of the directions, the loop component is capable of stretching at least to 2.0 times its relaxed length. The loop component is constructed of a neck-stretched non-woven material attached directly to an elastic substrate that is elastically stretchable in at least two directions. The resulting loop component is also capable of elastic stretching in at least two directions. Moreover as claimed (a mechanical fastening system), the loop component and hook component can be mated for secure engagement.

The stretch in the loop material advantageously allows flexibility so that as the loop material is stretched during use, only some of the points of engagement between the hooks and loops are separated when the product is stressed. Many of hooks that are disengaged from the loops are able to reattach to a different spot in the loop material as it contracts. This significantly reduces "pop opens" (abrupt disengagement of the fasteners) over conventional hook-and-loop fasteners, which tend to separate all at once.

This is a particularly important feature in disposable garments and especially, in training pants, which are

typically used by active toddlers. Toddlers are capable of many activities (e.g., running, jumping, squatting, bending) that stress the fastener system. In prior art fasteners, these stresses sometime resulted in the hook and loops fastening becoming disengaged, which compromises the effectiveness of the training pants. In other words, prior art training pants were more prone to leaking as a result of fastener system failure. The claimed fastening system is able to withstand greater stresses than the prior art fastening systems and thus, is less likely to leak. As can be appreciated, this is a substantial improvement over the prior art.

Specifically, claim 19 recites a mechanical fastening system for an article wherein the mechanical fastening system comprises:

- a) a loop component mountable on the article and capable of elastic stretching in at least two directions, said loop component being capable of being elastically stretched in at least one of the directions at least about 2.0 times a relaxed length of the loop component, said loop component comprising a neck-stretched non-woven material and an elastic substrate, said elastic substrate being elastically stretchable in at least two directions, said non-woven material being attached directly to the elastic substrate; and
- b) a hook component mountable on the article and capable of fastening engagement with the loop component to secure the article in a fastened configuration;
- c) whereby when the hook component is juxtaposed and engaged with at least a portion of the loop component, the loop component is stretchable during limited movement of the loop component relative to the hook component.

Claim 19 is submitted to be patentable over the references of record, and in particular U.S. Patent No. 5,910,136 (Hetzler). Hetzler fails to show or suggest a mechanical fastening system including a loop component that is mountable on an article, capable of elastic stretching in at least two directions, and is elastically stretchable to at least 2.0 times a relaxed length in at least one of the directions, and is constructed of a neck-stretched non-woven material attached directly to an elastic substrate.

Hetzler pertains to making a breathable, microporous film and laminate incorporating such a film. The patent has nothing to do with fastening systems generally or hook and loop fasteners in particular. References to fastening systems and hook and loop materials are made only in passing and, as will be explained more fully hereinafter, do not disclose or suggest a loop component that is capable of elastic stretching in at least two directions, and capable of stretching elastically to at least two times its relaxed length, as required by claim 19.

More specifically, Hetzler discloses oriented polymeric microporous (e.g., breathable) films with flexible polyolefins. At column 3, line 47 through column 7, line 3, Hetzler states that the "flexible polyolefins" can be used to initially form the film, and further disclose that the polyolefin resin may optionally include an elastomeric thermoplastic material. Flexible polyolefins may in some forms retain a measure of elasticity, but they are not nearly as elastic as the claimed loop component. The flexible polyolefins of Hetzler would almost certainly break if stretched to a length twice a relaxed length (as required by claim 19).

Moreover, there is a complete absence of any specific disclosure in Hetzler of a loop component that can be stretched in two directions. The film, or a breathable laminate constructed from the film, is disclosed as being useful in absorbent articles such as a diaper (80) as shown in Fig. 3, including using a non-woven portion of a laminate constructed from the film as the loop portion of a hook and loop combination. Hetzler discusses several different laminates that can be made, but never specifically describe a loop component stretchable in two directions. To anticipate a claim, a particular reference must clearly and unequivocally disclose the claimed invention or direct those skilled in the art to the invention without picking, choosing and combining various disclosures not directly related to each other by the cited reference. In re Arkley, 455 F.2d 586, 587 (CCPA 1972).

In In re Arkley, the cited reference disclosed the precursors to the claimed compound, but did not disclose the compound itself. However, the court found nothing in the reference that clearly and unequivocally led one of ordinary skill in the art to take the steps needed to form the compound from the precursors. Accordingly, the claim was not anticipated by the cited reference.

As in In re Arkley, there is no explicit disclosure in Hetzler of a loop component that is extensible in two directions and elastically stretchable in at least one of the two directions two times its relaxed length. The rejection is based on picking and choosing among disclosures that relate to the elastic substrate and disclosures that relate to various embodiments. Although use of one of the laminates as a loop component is mentioned in passing (col. 11, l. 22 - col. 12, 1. 2), there is absolutely no indication that this particular laminate is capable of stretching in two directions. There is

no disclosure that in the loop material version that the loop material can be elastically stretched to twice its relaxed length in at least one of the directions. There is no disclosure that the loop material has as one of its elements a neck-stretched loop material. To make such a rejection, the Examiner must pick and choose among the various disclosures in Hetzler (which is directed to producing breathable material, not a stretchable loop component) to reject claim 19. This stands in clear contradiction to In re Arkley.

None of the passages relied upon by the Office in paragraph 3 of the final Office action disclose the film and/or laminate as being elastically stretchable in multiple directions in its final (e.g., in use) form. The only passage in which the laminate is referred to as being stretchable at. all is at column 9, lines 26-36. This does not disclose that if the support layer attached to the elastic substrate is suitable for use as a loop material that bi-directional stretching can be achieved. Further, there is no disclosure that if such stretching could be achieved, it would be elastic (i.e., able to recover at least 50% of the amount by which the material is stretched) if stretched to two times its relaxed length.

The Examiner, as set forth in the last sentence of paragraph 3 of the Office action, relies on the teachings at column 7, lines 20-36 of Hetzler as disclosing a loop component that is elastically stretchable to at least twice a relaxed length. Hetzler defines "elastic" as any material that is elongatable to a length at least about 150 percent of its unbiased length. In other words, Hetzler defines "elastic" as any material that can be stretched at least about 1.5 times a relaxed length. Using the actual example provided in Hetzler (rather than a stated range not supported by

examples), a 1-inch sample of elastic material can be stretched to 1.5-inches, which is 1.5 times the original, relaxed length of 1-inch and not 2.0 times as recited in claim Thus, Hetzler does not disclose or suggest an elastic material that is elastically stretchable to at least 2.0 times its relaxed length.

As explained on page 35, line 26 through page 36, line 15 of the present application, one embodiment of the present invention can be stretched to a length about 200 percent of its initial, relaxed length. In the example provided in the application, the composite material (i.e., non-woven material and elastic substrate) has a relaxed length of 110 cm and is stretchable in the machine direction to 220 cm. Thus, the stretched length is 2.0 times the relaxed length. Claim 19 was previously amended to state "2.0" rather than "two" to emphasize the difference between 1.5 times the relaxed lengt:h in the prior art, and 2.0 times the relaxed length in the claimed invention. The stretch in the loop material allows flexibility so that as the loop material is stretched during use, only some of the points of engagement between the hooks and loops are separated when the product is stressed, and then some of the hooks are able to reattach to a different spot in the loop material as it contracts. This reduces "pop opens" as described above. Hetzler fails to disclose or suggest such a feature or the advantages of having such a feature.

For these reasons, claim 19 is unanticipated by and patentable over Hetzler.

Claims 3, 20-23, and 25 depend directly or indirectly from claim 19 and are submitted to be unanticipated by and patentable over the Hetzler for at least the same reasons.

Claim 25

Claim 25 depends from 19 and further requires the loop component be able to elastically stretch in at least one of the two directions 2.5 times its relaxed length. As explained on page 36, line 20 through page 37, line 26 of the present application, another embodiment of the present invention can be stretched to a width about 250 percent of its initial, relaxed width. In the example provided in the application, the composite material (i.e., non-woven material and elastic substrate) has a relaxed width of about 100 cm and is stretchable to a width of about 250 cm. Thus, the stretched width is 2.5 times the relaxed width. As mentioned above, the stretch in the loop material allows flexibility so that as the loop material is stretched during use, only some of the points of engagement between the hooks and loops are separated when the product is stressed, and then some of the hooks are able to reattach to a different spot in the loop material as it contracts. This reduces "pop opens."

Hetzler, for substantially the same reasons as set fort:h above with respect to claim 19, fails to show or suggest this additional feature. Accordingly, claim 25 is submitted as patentable over Hetzler for this additional reason.

Claims 3, 19-20, and 25 are patentable over U.S. Patent Nos. 5,883,028 (Morman '028), and thereby 5,116,662 (Morman '662) and 5,114,781 (Morman '781), in view of Hetzler.

Claim 19

Appellant disagrees with the Office's position that it would have been obvious in view of Hetzler to use the breathable elastic film/non-woven laminate of U.S. Patent No. 5,883,028 (Morman '028) to form a loop component of a mechanical fastening system for an article. Accordingly,

claim 19 is submitted as patentable over the combination of Morman '028 with Hetzler et al.

In determining whether a case of prima facie obviousness exists, it is necessary to ascertain whether the prior art teachings would appear to be sufficient to one of ordinary skill in the art to suggest making the claimed substitution or other modification. Obviousness can only be established by modifying the teachings of the prior art to produce the claimed invention where there is some teaching, suggestion, or motivation to do so found either in the references or in the knowledge generally available to one of ordinary skill in the art. M.P.E.P. §2143.01 citing In re Kotzab, 55 USPQ2d 1313, 1317 (Fed. Cir. 2000). The mere fact that a prior art reference may be modified to obtain the claimed invention does not make the claimed invention obvious if there is no suggestion or motivation in the reference to make the modification. In re Mills, 916 F.2d 680, 682, 16 U.S.P.Q.2d 1430, 1432 (Fed. Cir. 1990). The prior art must provide one of ordinary skill the motivation to make the proposed modifications. In re Lalu, 747 F.2d 703, 705, 223 USPQ 1257, 1258 (Fed. Cir. 1984). Such motivation is clearly lacking in this case.

The essence of claim 19 is that by providing a loop component capable of elastic stretching in at least two directions. The stretch in the loop material allows flexibility so that as the loop material is stretched during use, only some of the points of engagement between the hooks and loops are separated when the product is stressed, and then some of the hooks are able to reattach to a different spot in the loop material as it contracts. This reduces "pop opens." See, e.g., page 26, line 23 through page 27, line 1 of the pending application.

Both Morman '028 and Hetzler pertain to breathable (microporous) laminates and have nothing to do with mechanical fastening systems. They do not disclose loop components usable with hook components to form a fastening system, in which the loop components are stretchable in two directions. Because the cited references are not directed to fastening systems, they also fail to recognize any advantage associated with a loop component stretchable in two directions and thus, provide no suggestion for combination to produce a stretchable loop component.

Morman '028 discloses a breathable laminate comprising a non-woven web secured to an elastic film. The breathability of the laminate renders it useful as an outer cover for diapers and other personal care products, and surgical gowns. See column 1, lines 49-53 of Morman '028. There is no disclosure or teaching found in Morman '028 of forming a loop component of a mechanical fastening system that is elastically stretchable in at least two directions. Morman '662 and Morman '781 are incorporated by reference into Morman '028 for disclosing processes for making a multidirectional stretchable laminate from an elastic film and a necked nonwoven web. col. 12, lines 12-16. Morman '662 and Morman '781 also fail to disclose or teach forming a loop component of a mechanical fastening system that is elastically stretchable in at least two directions.

Hetzler discloses using the inelastic laminate disclosed therein as a loop component. However, there is no suggestion for making the inelastic loop component elastically stretchable in two directions, particularly where elasticity is maintained for stretching up to twice a relaxed length in at least one of the directions. Hetzler does not recognize the desirability or advantage of any such construction.

There is no suggestion or teaching found in either Morman '028 or Hetzler that would motivate one skilled in the art to replace the loop fastener of Hetzler with the laminate disclosed by Morman '028. That such a replacement can be made does not render the replacement obvious. Rather, there must be some motivation found in the references to make such a replacement. None is provided by either of the references. That is, neither of the references teaches the desire to provide a multi-direction elastically stretchable loop component to thereby increase engagement with the hook component. As stated previously, these references are concerned with producing breathable (microporous) laminates, not hook and loop fastening systems. Such motivation can only be improperly gleaned from the present application.

In addition, claim 19 requires that the loop component is capable of being elastically stretched in at least one of the directions at least about 2.0 times a relaxed length of the loop component. As mentioned above, Hetzler defines "elastic" as any material that can be stretched at least about 1.5 times a relaxed length. Morman '028 defines "elastic" at column 2, lines 58-67 (as cited by the Examiner) as any material that is elongatable to a length at least about 160 percent of its unbiased length. In other words, Morman '028 defines "elastic" as any material that can be stretched at least about 1.6 times a relaxed length. Using the actual example provided in Morman '028 (rather than a stated range not supported by examples), a 1-inch sample of elastic material can be stretched to 1.6-inches, which is 1.6 times the original, relaxed length of 1-inch and not 2.0 times as recited claim Thus, Morman '028 and Hetzler, whether considered alone or in combination, fail to teach or suggest a loop component

that is able to elastically stretch 2.0 times its relaxed length.

For these reasons, claim 19 is submitted to be nonobvious and patentable over the references of record.

Claims 3 and 20-23 and 25 depend directly or indirectly from claim 19 and are submitted to be nonobvious and patentable over the references of record for the same reasons as claim 19.

Claim 25

Claim 25 depends from claim 19 and further requires that the loop component be able to elastically stretch in at least one of the two directions 2.5 times its relaxed length. As mentioned above, the stretch in the loop material reduces "pop opens" (abrupt disengagement of the fasteners) over conventional hook-and-loop fasteners. Hetzler, Morman '028 and the other references of record fail to show or suggest this additional feature. Accordingly, claim 25 is submitted as patentable for this additional reason.

VIII. CONCLUSION

For all of the above reasons, appellant respectfully requests the Office's rejections be reversed and that claims 3, 19-20, and 25 be allowed.

The Commissioner is hereby authorized to charge \$500 for the appeal brief to Deposit Account No. 19-1345. The

Commissioner is hereby authorized to charge any additional fees which may be required to Deposit Account No. 19-1345.

Respectfully submitted,

F. James, & g. No. 33,716

SENNIGER POWERS

One Metropolitan Square, 16th Floor

St. Louis, Missouri 63102

(314) 231-5400

KFJ/PEB/bcw

Via Facsimile 571-273-8300

CLAIMS APPENDIX

1-2. Canceled.

(Previously presented) The mechanical fastening system of claim 20 wherein the loop component is made by stretching the non-woven material in the machine direction so as to neck down in the cross machine direction and then attaching the necked non-woven material directly to the elastic substrate while said substrate is stretched in the machine direction so that the loop component has gathers formed therein upon relaxing of the elastic substrate.

4-18. Canceled.

- 19. (Previously presented) A mechanical fastening system for an article, comprising:
- a loop component mountable on the article and capable of elastic stretching in at least two directions, said loop component being capable of being elastically stretched in at: least one of the directions at least about 2.0 times a relaxed length of the loop component, said loop component comprising a neck-stretched non-woven material and an elastic substrate, said elastic substrate being elastically stretchable in at least two directions, said non-woven material being attached directly to the elastic substrate; and

a hook component mountable on the article and capable of fastening engagement with the loop component to secure the article in a fastened configuration;

whereby when the hook component is juxtaposed and engaged with at least a portion of the loop component, the loop component is stretchable during limited movement of the loop component relative to the hook component.

- 20. (Previously presented) The mechanical fastening system set forth in claim 19 wherein the loop component has a machine direction and a cross-machine direction, the non-woven material being necked in the cross-machine direction of the loop component.
- (Previously presented) The mechanical fastening 21. system set forth in claim 19 in combination with the article, said article being for personal wear and comprising an inner layer for contact with a wearer's skin, at least a portion of the inner layer being liquid permeable, an outer layer in opposed relation with the inner layer, and an absorbent layer disposed between the inner layer and the outer layer, the loop component being formed separate from and mounted on the article.
- 22. (Previously presented) The combination set forth in claim 21 wherein the loop component is formed separate from and mounted on the outer layer of the article.
- (Previously presented) The combination set forth in claim 21 wherein the article further comprises longitudinally opposite end regions, the loop component being mounted on the article generally at one of said end regions and the hook component being mounted on the article generally at the opposite one of said end regions.
 - 24. Canceled.
- (Previously presented) A mechanical fastening system as set forth in claim 19 wherein said loop component is capable of being elastically stretched in at least one of the

directions at least about 2.5 times a relaxed length of the loop component.

EVIDENCE APPENDIX

None.

RELATED PROCEEDINGS APPENDIX

None.